

# Emission Mitigation Certificate

**Issue Date:** 01.03.2024  
**Certificate Number:** CCP/2475A

## EASYFLYERS Logistics limited

Lufthansa Group and Compensaid hereby guarantee the purchase of **335 kg** of Sustainable Aviation Fuel on behalf of **EASYFLYERS Logistics limited** resulting in an emission mitigation of at least **1,001 kg CO<sub>2</sub>e\*** in comparison to conventional (fossil) jet fuel based on a Well-to-Wheel assessment. This fuel has not been derived from Palm Oil or Palm Fatty Acid Distillates and the resulting mitigation is exclusively allocated to the aforementioned company. The fuel manufacturer is certified according to ISCC EU and complies with the requirements of the RED and the certification system ISCC EU which is approved by the European Commission.

**Total Mass:** 335 kg  
**Total Energy Equivalent:** 14,338 MJ  
**WTW emission factor:** max. 17,46 g CO<sub>2</sub>e\*/MJ  
**Mitigation in percent (WTW basis):** min. 80 %  
**Mitigation (absolute):** min. 1,001 kg CO<sub>2</sub>e\*  
**Fossil fuel reference:** min. 1,252 kg CO<sub>2</sub>e\*  
**Uplift location:** Frankfurt (FRA)

CO<sub>2</sub>e\* mitigation

**1,001 kg**

Amount of SAF purchased

**335 kg**




**Jan Pechstein**

Head of Corporate Emissions Management & Sustainable Aviation Fuels, Lufthansa Group



**Katja Kleffmann**

Head of Fuel Management Supply, Lufthansa Group



**Müller-BBM Cert Umweltgutachter GmbH**

Independent auditor for verification of this certificate and the associated calculation principle

\* Includes CO<sub>2</sub>-equivalents from production, transport and distribution of the fuel; excludes CO<sub>2</sub>-equivalents from combustion.

### Calculation based on:

emission factor SAF (TTW): 0 g CO<sub>2</sub>e/MJ; emission factor fossil fuel (TTW, acc. Regulation (EU) 2018/2066): 3,150 g CO<sub>2</sub>/kg Jet-A1; energy factor (acc. DIN 16258): 44.1 MJ/kg Jet-A1; emission factor SAF (WTT): as given in NABISY Certificate or Refiner's Biofuel Sustainability Statement; emission factor fossil fuel (WTT, acc. DIN 16258): 15.9 g CO<sub>2</sub>e/MJ; lower heating value (acc. ASTM D1655): min. 42.8 MJ/kg